Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: JANUARY 30, 2020						
Owner Information						
Owner Name: MIDDLEBROOK PINES CONDOS CASE#: 20200130-WMIR-43		Contact Person: KEITH KIEBZAK				
Address: 5339, 5341, 5343, 5345 BAM			Home Phone:			
City: ORLANDO	Zip: 32811			2-2622		
County: ORANGE	FL		Cell Phone:			
Insurance Company:			Policy #:			
Year of Home: 1986	# of Stories: 2		Email: KLMGMTGRO	OUP@AOL.COM		
NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.						
1. <u>Building Code</u> : Was the structure built the HVHZ (Miami-Dade or Broward cou	ınties), South Florida B	Building Code (SFBC-9	4)?			
a date after 3/1/2002: Building Perm				11		
B. For the HVHZ Only: Built in con						
provide a permit application with a c			on Date (MM/DD/YYYY)/_			
C. Unknown or does not meet the re	quirements of Answer	"A" or "B"				
2. Roof Covering: Select all roof covering types in use. Provide the permit application date OR FBC/MDC Product Approval number OR Year of Original Installation/Replacement OR indicate that no information was available to verify compliance for each roof covering identified.						
	Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance		
1. Asphalt/Fiberglass Shingle		<u> </u>				
2. Concrete/Clay Tile/						
□	/					
				Ħ		
5. Membrane				H		
	/			H		
A. All roof coverings listed above meet the FBC with a FBC or Miami-Dade Product Approval listing current at time of						
installation OR have a roofing permit application date on or after 3/1/02 OR the roof is original and built in 2004 or later.						
B. All roof coverings have a Miami-Dade Product Approval listing current at time of installation OR (for the HVHZ only) a roofing permit application after 9/1/1994 and before 3/1/2002 OR the roof is original and built in 1997 or later.						
C. One or more roof coverings do not meet the requirements of Answer "A" or "B".						
D. No roof coverings meet the requi	-					
3. Roof Deck Attachment: What is the weakest form of roof deck attachment?						
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood						
shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent						
mean uplift less than that required for Options B or C below.						
B. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of						
24"inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives,						
other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.						
C. Plywood/OSB roof sheathing with a minimum thickness of 7/16"inch attached to the roof truss/rafter (spaced a maximum of						
24"inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove						
decking with a minimum of 2 nails	-		=			
Inspectors Initials DKS Property Address 5339, 5341, 5343, 5345 BAMBOO CT - BLDG 43 ORLANDO FL 32811						

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at 182 psf.	least
D. Reinforced Concrete Roof Deck.	
E. Other:	
F. Unknown or unidentified.	
G. No attic access.	
4. Roof to Wall Attachment: What is the WEAKEST roof to wall connection? (Do not include attachment of hip/valley jacks w 5 feet of the inside or outside corner of the roof in determination of WEAKEST type)	ıthın
A. Toe Nails	
Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attach the top plate of the wall, or	ied to
Metal connectors that do not meet the minimal conditions or requirements of B, C, or D	
Minimal conditions to qualify for categories B, C, or D. All visible metal connectors are:	
Secured to truss/rafter with a minimum of three (3) nails, and	
Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap fr the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.	om
B. Clips	
Metal connectors that do not wrap over the top of the truss/rafter, or	
Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the position requirements of C or D, but is secured with a minimum of 3 nails.	e nail
C. Single Wraps	
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured v minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.	vith a
D. Double Wraps	
Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bon- beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or	
Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall both sides, and is secured to the top plate with a minimum of three nails on each side.	on
E. Structural Anchor bolts structurally connected or reinforced concrete roof.	
F. Other:	
G. Unknown or unidentified	
H. No attic access	
	-11 of
5. <u>Roof Geometry</u> : What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or was the host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).	111 01
A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter. Total length of non-hip features: feet; Total roof system perimeter: feet	
B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft	
C. Other Roof Any roof that does not qualify as either (A) or (B) above.	
6. Secondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR)	a tha
A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the	5 the
dwelling from water intrusion in the event of roof covering loss.	
B. No SWR. C. Unknown or undetermined.	
C. Challown of undetermined.	
Inspectors Initials DKS Property Address 5339, 5341, 5343, 5345 BAMBOO CT - BLDG 43 ORLANDO FL 326	311

Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. Opening Protection: What is the weakest form of wind borne debris protection installed on the structure? First, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable. Non-Glazed Opening Protection Level Chart **Glazed Openings** Openings Place an "X" in each row to identify all forms of protection in use for each Windows opening type. Check only one answer below (A thru X), based on the weakest Entry Glass Garage Garage or Entry Skylights form of protection (lowest row) for any of the Glazed openings and indicate Doors **Block** Doors Doors Doors the weakest form of protection (lowest row) for Non-Glazed openings. N/A Not Applicable- there are no openings of this type on the structure Α Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights) В Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights) Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007 Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E D 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance Opening Protection products that appear to be A or B but are not verified Ν Other protective coverings that cannot be identified as A, B, or C х No Windborne Debris Protection A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above). Miami-Dade County PA 201, 202, and 203 Florida Building Code Testing Application Standard (TAS) 201, 202, and 203 American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996 Southern Standards Technical Document (SSTD) 12 For Skylights Only: ASTM E 1886 and ASTM E 1996 For Garage Doors Only: ANSI/DASMA 115 A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, or X in the table above A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above): ASTM E 1886 and ASTM E 1996 (Large Missile – 4.5 lb.) SSTD 12 (Large Missile – 4 lb. to 8 lb.) For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile - 2 to 4.5 lb.) B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above Exterior Opening Protection- Wood Structural Panels meeting FBC 2007 All Glazed openings are covered with plywood/OSB meeting the requirements of Table 1609.1.2 of the FBC 2007 (Level C in the table above). C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above C.3 One or More Non-Glazed openings is classified as Level N or X in the table above Inspectors Initials DKS Property Address 5339, 5341, 5343, 5345 BAMBOO CT - BLDG 43 32811 **ORLANDO** FL

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

N. Exterior Opening Protection (unverified shutter s			
protective coverings not meeting the requirements of Ar		stems that appear to meet Answ	wer "A" or "B"
with no documentation of compliance (Level N in the ta	· · · · · · · · · · · · · · · · · · ·		
N.1 All Non-Glazed openings classified as Level A, B, C, o		• •	
N.2 One or More Non-Glazed openings classified as Level label table above	O in the table above, and no No	on-Glazed openings classified as I	Level X in the
N.3 One or More Non-Glazed openings is classified as Leve	ol X in the table above		
		1 V ' 41 . 4.1.11	
X. None or Some Glazed Openings One or more Glaze	ed openings classified and L	evel A in the table above.	
MITIGATION INSPECTIONS MUST B	E CERTIFIED RY A OUAI	LIFIED INSPECTOR	
Section 627.711(2), Florida Statutes, provi	~		
Qualified Inspector Name:	License Type:	License or Certificate #:	
DEBORAH SIEBERN Inspection Company:	Home Inspector	HI-139	
AVALON HOME INSPECTIONS, LLC		407-435-5155	
Qualified Inspector – I hold an active license as a	(check one)		
Home inspector licensed under Section 468.8314, Florida Statute		tory number of hours of hurricana	mitigation
training approved by the Construction Industry Licensing Board			mitigation
Building code inspector certified under Section 468.607, Florida		•	
General, building or residential contractor licensed under Section			
Professional engineer licensed under Section 471.015, Florida St	atutes.		
Professional architect licensed under Section 481.213, Florida St			
Any other individual or entity recognized by the insurer as posse	ssing the necessary qualification	ons to properly complete a uniform	n mitigation
verification form pursuant to Section 627.711(2), Florida Statute			C
Individuals other than licensed contractors licensed under	Section 489.111, Florida S	tatutes, or professional engin	eer licensed
under Section 471.015, Florida Statues, must inspect the str	uctures personally and no	t through employees or othe	r persons.
Licensees under s.471.015 or s.489.111 may authorize a dire	ect employee who possesse	es the requisite skill, knowled	ge, and
experience to conduct a mitigation verification inspection.			
	nd I personally performed	I the inspection or (licensed	
(print name)	(\	
contractors and professional engineers only) I had my emplo	(print name) perform the inspection of inspector)	
and I agree to be responsible for his/her work.	(print nume	or inspector)	
Qualified Inspector Signature:	Date: JANU	ARY 30, 2020	
Quanticu Inspector Signature:	. Date		
An individual or entity who knowingly or through gross ne	gligence provides a false o	r fraudulent mitigation verif	ication form is
subject to investigation by the Florida Division of Insurance			
appropriate licensing agency or to criminal prosecution. (S certifies this form shall be directly liable for the misconduc			
performed the inspection.	t of employees as if the aut	morized midgadon inspector	personany
Homeowner to complete: I certify that the named Qualified	Inspector or his or her emp	ployee did perform an inspection	on of the
residence identified on this form and that proof of identification	1 was provided to me or my	Authorized Representative.	
Signature: I	Date: JANUARY 30, 202	<u> </u>	
, .			
An individual or entity who knowingly provides or utters a	false or fraudulent mitiga	tion verification form with t	he intent to
obtain or receive a discount on an insurance premium to w			
of the first degree. (Section 627.711(7), Florida Statutes)			
The definitions on this form are for inspection numbers and	y and gannat he ward to a	ortify any product or const	ection foot
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	iy and cannot be used to c	ermy any product or constru	chon leature
	FOAF DANIDOO OT DUDO (ODI ANDO	EI 22044
Inspectors Initials DKS Property Address 5339, 5341, 5343	, 5345 BAMBOO CT - BLDG 43	3 ORLANDO	FL 32811 -
*This verification form is valid for up to five (5) years prov	ided no material changes	have been made to the struct	ure or

inaccuracies found on the form. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155



ADDRESS VERIFICATION



ROOF - CONCRETE WITH TPO COVERING



ADDRESS VERIFICATION



FRONT ELEVATION



ADDRESS VERIFICATION



FRONT ELEVATION



ADDRESS VERIFICATION



FRONT ELEVATION



ADDRESS VERIFICATION



FRONT ELEVATION



MANSARD WALLS REPLACED 2018